

25

PW

GLASS POCKET DOOR SINGLE





Note: Non standard sizes on request

PLEASE NOTE INBUILT TOLERANCE

If setting out your studwork before delivery of your frame please note there is approximately an 8mm tolerance built into the height of these pocket door systems which you will need to take into account. Packers may be required to accommodate for this gap if you are unable to adjust the studwork above the system.

Note: Frame should be installed at finished floor level.

FRAMES FOR SINGLE DOORS			DOOR PANELS UK	
MAX. PASSAGE SIZE PW x PH	OVERALL DIMENSION W x H	FINISHED WALL FW	DW	DH
661 x 1971	1455 x 2056	95 - 100 -115 - 125	2ft. 3in. x 6ft. 6in. (686 x 1981 mm)	
737 x 1971	1631 x 2056	95 - 100 -115 - 125	2ft. 6in. x 6ft. 6in. (762 x 1981 mm)	

Dimensions are given in mm



NOTES

- ▶ Includes full timber lining kit for a professional finish.
- Plasterboard and final architrave not supplied.
- When fitting flush pull handles we recommend the stop be regulated so the door protrudes from the pocket to avoid risk to fingers.
- Should the door be set to enter the pocket completely we do not accept any liability.
- Install at finished floor level.
- Nominal size.



ACCESSORIES

► ECLISSE BIAS®

Soft close up to 40 kg with anti-slam*

► ECLISSE BIAS® DS

Bi-directional soft close up to 40 kg with anti-slam*

Linear motor open/close

* Above a door panel weight of 40 kg the anti-slam will still work but the door may not close completely against the doorpost of its own accord.



